

Kwik-Guide: ACCORDION PARTITIONS

SPECIFICATIONS	MODELS	VL-8	VL-6	VL-2	MK-X	MK-XX
CONFIGURATION	Single	Yes	Yes	Yes	Yes	Yes
	Pairs	Yes	Yes	Yes	Yes	Yes
	Multiple (intersecting)	Yes	Yes	Yes	Yes	Yes
OPERATION	Manual	Yes	Yes	Yes	Yes	Yes
SOUND CONTROL	STC Ratings	40	38	35	Non-Acoustic	Non-Acoustic
SUSPENSION	Top Supported	Yes	Yes	Yes	Yes	Yes
DIMENSIONS	Extended Width	6.0"	5.0"	5.0"	3.25"	5.0"
	Stacked Width	10.0"	9.5"	9.5"	5'25"	9'0"
	Max. Partition Height	16'-0"	16'-0"	16'-0"	12'-0"	16'-0"
	Max . Partition Width	25'-0"	25'-0"	25'-0"	16'-0"	25'-0"
	Stack Depth: inches Per ft. of Width	2.6	2	2	2	1.75 + 2.5
WEIGHT	Lbs. Per. / Sq. Foot	3.65	3.15	2.65	7.35	7.5 - 8.0
FRAME TYPE	Full Steel Pantograph	Yes	Yes	Yes	Half-Pantograph	Yes
FINISH OPTIONS	Standard - Class A Rated	21 Oz. Vinyl / 23 oz. Carpet	21 Oz. Vinyl / 23 oz. Carpet	21 Oz. Vinyl / 23 oz. Carpet	21 Oz. Vinyl / 23 oz. Carpet	21 Oz. Vinyl / 23 oz. Carpet
	Optional - C.O.M.	Requires KW Approval	Requires KW Approval	Requires KW Approval	Requires KW Approval	Requires KW Approval
SECURITY	Locking Options	One / Both Sides	One / Both Sides	One / Both Sides	One / Both Sides	One / Both Sides
HARDWARE	Pull Handle	Chrome finish / Positive Latching	Chrome finish / Positive Latching	Chrome finish / Positive Latching	Chrome finish / Positive Latching	Chrome finish / Positive Latching
SEALS	Type / Material	Multi-ply, Rubberized Continuous Sweep Seal	Multi-ply, Rubberized Continuous Sweep Seal	Multi-ply, Rubberized Continuous Sweep Seal	Multi-ply, Rubberized Continuous Sweep Seal	Multi-ply, Rubberized Continuous Sweep Seal