Koroseal®

3875 Embassy Parkway Fairlawn, OH 44333 855.753.5474 · koroseal.com

PATTERNS

Kashi • Linden • Patana • Tahiti Ramie • Orleans • Hurstbourne Bengal • Linden II • Lino

US UNITS METRIC UNITS

Total Weight 20.0 oz. PLY 620 g PLM

Roll Width 52" – 54" 132 cm – 137 cm

Backing Woven (Osnaburg)

Tensile (Minimum) $50 \times 55 \text{ lb}_f$ $222 \times 245 \text{ N}$ Tear (Minimum) $25 \times 25 \text{ lb}_f$ $111 \times 111 \text{ N}$

Federal Spec CCC-W-408D, Type II

WA Spec. WA-101, Type II

ASTM F-793 Category V, Type II

Fire Testing NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹

Class A Rating
Flame Spread – 10
Smoke Developed – 5
NFPA 286 Corner Burn Test²

Meets requirements for Flame Spread, Smoke Developed and Flashover

CE Certification EU Classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

Repeat Vertical N/A

Horizontal N/A Nominal Pattern Width 51"

Match Information Reverse Hang, Random Match – all patterns except:

Linden II: Random Match, Non-Reverse Hang

- 1. When applied to GRC board with A-848-B adhesive
- 2. When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

Kwik-WallTM standard and upgrade vinyls are supplied by Koroseal®. Both Kwik-Wall and Koroseal support sustainable construction practices offering *option* e^{TM} wallcoverings that meet the same characteristics of Type II vinyl but made from recycled materials that contribute to LEED® MR 4 & EQ 4. Contact Kwik-Wall for availability and pricing impacts.

Actual color provided may vary from swatch shown due to dye-lot variations. Room lighting may also change the color's appearance.



