## Koroseal®

3875 Embassy Parkway Fairlawn, OH 44333 855.753.5474 → koroseal.com

## PATTERNS White Creek • Lineage Destiny • Galerie

		US UNITS	METRIC UNITS
Total Weight		20.0 oz. PLY	620 g PLM
Roll Width		52" – 54"	132 cm – 137 cm
Backing		Woven (Osnaburg)	
Tensile (Minimum)		50 x 55 lb <sub>f</sub>	222 x 245 N
Tear (Minimum)		25 x 25 lb <sub>f</sub>	111 × 111 N
Federal Spec		CCC-W-408D, Type II	
WA Spec.		WA-101, Type II	
ASTM F-793		Category V, Type II	
Fire Testing		NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating Flame Spread – 10 Smoke Developed – 5 NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification		EU Classification in accordance with EN 15102:2007 + A1:2011	
Indoor Air Quality		California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51" Reverse Hang, Random Match – all patterns except: Lineage: Random Match, Non-Reverse Hang	
1. When applied to GRC board with A-848-B adhesive			
2. When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive			

**Kwik-Wall™** standard and upgrade vinyls are supplied by Koroseal®. Both Kwik-Wall and Koroseal support sustainable construction practices offering *option* e<sup>™</sup> wallcoverings that meet the same characteristics of Type II vinyl but made from recycled materials that contribute to LEED® MR 4 & EQ 4. Contact Kwik-Wall for availability and pricing impacts.

Actual color provided may vary from swatch shown due to dye-lot variations. Room lighting may also change the color's appearance.



4650 Industrial Ave., Springfield, IL 62703 (800) 280-5945 • kwik-wall.com



USGBC® and the related logo are trademarks owned by the U.S. Green Building Council® and are used with permission.