

SPECIFICATIONS	FlexTact Tactical Walls
PANEL CONSTRUCTION	Precision 16 ga. welded steel frames of 3" [76mm] minimum profile.
TRACK	6063-T6 Clear Anodized Aluminum, on standard 4' x 4' grid layout with "X", "L" and "T" track intersections
PANEL CARRIERS	Dual, counter-rotating steel wheels with precision-ground radial bearings.
PANEL OPERATION	Multi-directional, Individual panels
PANEL FACES	Field replaceable medium density fiberboard (MDF)
STANDARD PANEL FINISHES	Wilsonart (R) solid color, impact-resistant high-pressure laminate
PANEL STACKING CONFIGURATIONS	Offset "F" and "H" single or multiple stacks, remote stacking
MAXIMUM OPENING WIDTH	Unlimited, except when using Unispan support (<i>40' dimension on single side</i>).
PANEL TRIM	Protective edge trim
PASS DOOR PANELS	Std. 2'-8" x 6'-8" with 20 ga. steel faces, 180 degree door swing, with roller latch and adjustable, concealed door closers
VERTICAL PANEL SEALS	4" PVC seals allow panels to pass through 90-degree intersections without disassembly of adjacent panels
BOTTOM SEALS	Mechanical, retractable, constant-force-contact seal with up to 100 lbs. of downward seal force for panel stability
OPTIONAL FLEXTACT PARTITION SUPPORT	Kwik-Wall Unispan engineered truss support