



Operable Walls by Kwik-Wall

Technical Data

3000 SERIES • **2000 SERIES** • HUF COR 600 SERIES

MODEL 2020 — INDIVIDUAL, MULTI-DIRECTIONAL PANELS

SECTION 10 22 26 OPERABLE PARTITIONS
SECTION 10 22 39 FOLDING PANEL PARTITIONS



Overview

Panel Type

- ☐ Individual Panels Curve & Diverter
☒ Individual Panels – Multi Directional
☐ Hinged-Paired
☐ Continuously-Hinged

Partition Operation

- ☒ Manual
☐ Electric

Stacking Configurations

- ☐ Centerline
☒ Offset
☒ Remote
☐ Bi-Parting

STC Options

A=Acoustic Substrate S=Steel Skin

- ☒ 42A ☒ 49S
☒ 45A ☒ 50A
☒ 49A ☒ 51S

Panel Finishes

- ☒ Vinyl ☒ High Pressure Laminate
☒ Fabric ☒ Wood Veneer
☒ Carpet ☒ Customer Supplied*

* Material subject to Kwik-Wall approval

Vertical Panel Joints

- ☒ Trimless
☒ Capped Trim

Top Seals

- ☒ Fixed
☒ Operable

Bottom Seals

- ☐ Fixed ☒ Automatic
☒ Adjustable Fixed ☐ Extended
☒ Operable

Available Options

Storage pocket doors; ADA Pass Doors – (single, double with panic hardware, concealed door closures & exit signs); dry marker surfaces; insulated glass unit inserts; (GL Panels); tack surfaces.

KWIK-WALL's Model 2020 / 2020GL – featuring individual, multi-directional panels capable of making 90° turns at X, L, or T track intersections in room division applications up to 16'-2" [9144] in height. With STC options from 42-51, 2000 Series Operable Walls offer industry-leading premium sound control.

Model **2020** construction features panels that are 3" [76.2] thick, manufactured of a durable roll-formed steel frame, and standard steel skins for maximum durability and sound control. Optional acoustical glass inserts, (**2020GL**) are available and achieve 38 STC sound control.



2000 Series Panel Weights

STC	lbs./sq.ft.	Kg/m2
42A	6.5 lbs./sq. ft.	[32 kg/m2]
45A	8.5 lbs./sq. ft.	[41 kg/m2]
49A	9.0 lbs./sq. ft.	[44 kg/m2]
49S	10.9 lbs./sq. ft.	[53 kg/m2]
50A	9.0 lbs./sq. ft.	[44 kg/m2]
51S	11.0 lbs./sq. ft.	[54 kg/m2]



More Information