




# Operable Walls by Kwik-Wall

## Technical Data

3000 SERIES • **2000 SERIES** • HUF COR 600 SERIES

### MODEL 2050 — Continuously-Hinged Electric Panels

SECTION 10 22 26 OPERABLE PARTITIONS  
SECTION 10 22 39 FOLDING PANEL PARTITIONS



#### Overview

##### Panel Type

- ☐ Individual Panels Curve & Diverter  
☐ Individual Panels – Multi Directional  
☐ Hinged-Paired  
☒ Continuously-Hinged

##### Partition Operation

- ☐ Manual  
☒ Electric

##### Stacking Configurations

- ☒ Centerline  
☐ Offset  
☐ Remote  
☒ Bi-Parting

##### STC Options

A=Acoustic Substrate S=Steel Skin

- ☒ 42A      ☒ 49S  
☒ 45A      ☒ 50A  
☒ 49A      ☒ 51S

##### Panel Finishes

- ☒ Vinyl      ☒ High Pressure Laminate  
☒ Fabric      ☒ Wood Veneer  
☒ Carpet      ☒ Customer Supplied\*

\* Material subject to Kwik-Wall approval

##### Vertical Panel Joints

- ☒ Trimless  
☒ Capped Trim

##### Top Seals

- ☒ Fixed  
☐ Operable

##### Bottom Seals

- ☐ Fixed      ☐ Automatic  
☒ Adjustable Fixed      ☐ Extended  
☐ Operable

##### Available Options

Storage pocket doors; ADA Pass Doors – (single, concealed door closures & exit signs); dry marker surfaces; insulated glass unit inserts; (GL Panels); tack surfaces.

**KWIK-WALL's Model 2050 / 2050GL** – features electric operation for fully automatic setup. With centerline support, continuously-hinged electric operable walls are ideally suited for large, tall openings for straight-run room division applications up to 14'-2" [4318]. With STC options from 46 to 51, Series 2000 operable walls offer industry-leading premium sound control.

**Model 2050** construction features panels that are 3" thick [76.2] thick, manufactured of a durable roll-formed steel frame with standard steel skins, or with optional acoustic substrate to form a rigid, unitized and structural panel for maximum sound control and durability. Optional insulated glass units (**2050 GL**) are available with 38 STC sound control.



2000 Series Panel Weights

STC	lbs./sq.ft.	Kg/m2
42A	6.5 lbs./sq. ft.	[32 kg/m2]
45A	8.5 lbs./sq. ft.	[41 kg/m2]
49A	9.0 lbs./sq. ft.	[44 kg/m2]
49S	10.9 lbs./sq. ft.	[53 kg/m2]
50A	9.0 lbs./sq. ft.	[44 kg/m2]
51S	11.0 lbs./sq. ft.	[54 kg/m2]



2050/2050GL

More Information