



Operable Walls by Kwik-Wall Technical Data

3000 SERIES • **2000 SERIES** • HUF COR 600 SERIES

2000 SERIES — Pocket Doors

SECTION 10 22 26 OPERABLE PARTITIONS
SECTION 10 22 39 FOLDING PANEL PARTITIONS



Overview

Pocket Door Types

- ☒ Bi-Fold Doors w/ Bulb Seal
- ☒ Single Door w/ Bulb Seal
- ☒ Single Door w/ Expander
- ☒ Double Doors w/ Lap Trim
- ☒ Double Doors w/ Expander
- ☒ Double Doors w/Expander & Interlock Switches [2050 model]

Operation

- ☒ Manual
- ☒ Electric: Safety Interlock disables electric operable wall operation when pocket doors are closed.

STC Options

A=Acoustic Substrate S=Steel Skin

- ☒ 42A ☒ 49S
- ☒ 45A ☒ 50A
- ☒ 49A ☒ 51S

Panel Finishes

- ☒ Vinyl ☒ High Pressure Laminate
 - ☒ Fabric ☒ Wood Veneer
 - ☒ Carpet ☒ Customer Supplied*
- * Material subject to Kwik-Wall approval

Vertical Panel Joints

- ☒ Trimless
- ☒ Capped Trim

Top Seals

- ☒ Fixed: seals against pocket door header trim
- ☐ Operable

Bottom Seals

- ☒ Fixed ☐ Automatic
- ☐ Adjustable Fixed ☐ Extended
- ☐ Operable

Security Hardware Options

- ☒ Keyed Cylinder Lock with adjustable concealed vertical rod interfacing with strike plate attached to finished floor.
- ☒ Master Keyed Cylinder Lock (optional), furnished by others and installed by Kwik-Wall as noted on submittal shop drawings.

KWIK-WALL's **2000 Series Pocket Doors** close off your operable wall storage area when panels are not. Constructed with the same materials as our 2000 Series operable wall panels, **2000 Series** pocket doors hide the operable wall panels and can serve as the perimeter wall for your final closure to seal against. In very wide openings, sealing to the face of the pocket door can eliminate panels without compromising the acoustic integrity of your operable wall.

Series **2000** Pocket Doors are 3" [76.2] thick, manufactured of a durable roll-formed steel frame, and standard steel skins for maximum durability and sound control.



2000 Series Panel Weights

STC	lbs./sq.ft.	Kg/m2
42A	6.5 lbs./sq. ft.	[32 kg/m2]
45A	8.5 lbs./sq. ft.	[41 kg/m2]
49A	9.0 lbs./sq. ft.	[44 kg/m2]
49S	10.9 lbs./sq. ft.	[53 kg/m2]
50A	9.0 lbs./sq. ft.	[44 kg/m2]
51S	11.0 lbs./sq. ft.	[54 kg/m2]



More Information