




Operable Walls by Kwik-Wall Technical Data

3000 SERIES • 2000 SERIES • HUF COR 600 SERIES

MODEL 3010 — Individual Panels, Curve and Diverter

SECTION 10 22 26 OPERABLE PARTITIONS
SECTION 10 22 39 FOLDING PANEL PARTITIONS



Overview

Panel Type

- ☒ Individual Panels Curve & Diverter
☐ Individual Panels – Multi Directional
☐ Hinged-Paired
☐ Continuously-Hinged

Partition Operation

- ☒ Manual
☐ Electric

Stacking Configurations

- ☐ Centerline
☒ Offset
☒ Remote
☐ Bi-Parting

STC Options

A=Acoustic Substrate S=Steel Skin

- ☒ 46A ☒ 50S
☒ 46S ☒ 52S
☒ 48A ☐ 54S
☒ 50A ☒ 56S

Panel Finishes

- ☒ Vinyl ☒ High Pressure Laminate
☒ Fabric ☒ Wood Veneer
☒ Carpet ☒ Customer Supplied*
 * Material subject to Kwik-Wall approval

Vertical Panel Joints

- ☒ Trimless
☒ Capped Trim

Top Seals

- ☒ Fixed
☐ Operable

Bottom Seals

- ☐ Fixed ☒ Automatic
☒ Adjustable Fixed ☒ Extended
☒ Operable

Available Options

Storage pocket doors; ADA Pass Doors – (single, double with panic hardware, concealed door closures & exit signs); invisible hinges; dry marker surfaces; insulated glass unit inserts; (GL Panels); tack surfaces.

KWIK-WALL's Model 3010 / 3010GL – Individual panels with pre-programmed-travel paths utilizing ultra-smooth radius curve and diverter track system which eliminates operator set up errors. Ideally suited for complex layouts and stacking configurations in applications up to 30'-0" [9144] in height. STC options from 46-56, Series 3000 operable walls offer industry-leading sound control

Model **3010** construction features panels that are 4" [101.6] thick, with a frame manufactured of durable roll-formed steel, and for maximum strength and sound control steel skins are standard. Optional insulated glass units 3010 GL are available with 43 and 48 STC.



Radius Curve
& Diverter Track

3000 Series Panel Weights

STC	lbs./sq.ft.	Kg/m2
46A	6.6 lbs./sq.ft	[32 kg/m2]
46S	8.5 lbs./sq.ft	[41 kg/m2]
48A	7.5 lbs./sq.ft	[37 kg/m2]
50A	9.0 lbs./sq.ft	[44 kg/m2]
50S	9.5 lbs./sq.ft	[46 kg/m2]
52S	9.5 lbs./sq.ft	[46 kg/m2]
56S	12.9 lbs./sq.ft	[63kg/m2]



More Information