




Operable Walls by Kwik-Wall

Technical Data

3000 SERIES • 2000 SERIES • HUF COR 600 SERIES

MODEL 3050 — Continuously-Hinged Electric Panels

SECTION 10 22 26 OPERABLE PARTITIONS
SECTION 10 22 39 FOLDING PANEL PARTITIONS



Overview

Panel Type

- ☐ Individual Panels Curve & Diverter
☐ Individual Panels – Multi Directional
☐ Hinged-Paired
☒ Continuously-Hinged

Partition Operation

- ☐ Manual
☒ Electric

Stacking Configurations

- ☒ Centerline
☐ Offset
☐ Remote
☒ Bi-Parting

STC Options

A=Acoustic Substrate S=Steel Skin

- ☒ 46A ☒ 50S
☒ 46S ☒ 52S
☒ 48A ☐ 54S
☒ 50A" ☒ 56S

Panel Finishes

- ☒ Vinyl ☒ High Pressure Laminate
☒ Fabric ☒ Wood Veneer
☒ Carpet ☒ Customer Supplied*
 * Material subject to Kwik-Wall approval

Vertical Panel Joints

- ☒ Trimless
☒ Capped Trim

Top Seals

- ☒ Fixed
☐ Operable

Bottom Seals

- ☐ Fixed ☐ Automatic
☒ Adjustable Fixed ☐ Extended
☐ Operable

Available Options

Storage pocket doors; ADA Pass Doors – (single, concealed door closures & exit signs); invisible hinges; dry marker surfaces; insulated glass unit inserts; (GL Panels); tack surfaces.

KWIK-WALL's Model 3050 / 3050GL – features electric operation for automatic set up. With centerline support, **3050** and **3050 GL** continuously-hinged electric operable walls are ideally suited for large, tall openings for straight-run room division applications up to 24'-2" [7366] with steel skins, and 14'-2" with acoustic substrate [4318]. With STC options from 46-56, 3000 Series Operable Walls offer industry-leading premium sound control.

Model 3050 construction features panels that are 4" [101.6] thick, manufactured of a durable roll-formed steel frame, and standard steel skins for maximum durability and sound control. Optional acoustical glass inserts, (**3050GL**) are available and achieve 43 and 48 STC sound control.



3000 Series Panel Weights

STC	lbs./sq.ft.	Kg/m2
46A	6.6 lbs./sq.ft	[32 kg/m2]
48A	7.5 lbs./sq.ft	[37 kg/m2]
50A	9.0 lbs./sq.ft	[44 kg/m2]
46S	8.5 lbs./sq.ft	[41 kg/m2]
50S	9.5 lbs./sq.ft	[46 kg/m2]
52S	9.5 lbs./sq.ft	[46 kg/m2]
56S	12.9 lbs./sq.ft	[63kg/m2]



More Information