



MODEL 641 — Individual Panels

SECTION 10 22 26 OPERABLE PARTITIONS
SECTION 10 22 39 FOLDING PANEL PARTITIONS



Overview

Panel Type

- Individual Panels Curve & Diverter
- Individual Panels – Multi Directional
- Hinged-Paired
- Continuously-Hinged

Partition Operation

- Manual
- Electric

Stacking Configurations

- Centerline
- Offset
- Remote
- Bi-Parting

STC Options

A=Acoustic Substrate S=Steel Skin

- 50A
- 52S
- 54A
- 56S

Panel Finishes

- Vinyl
 - Fabric
 - Carpet
 - High Pressure Laminate
 - Wood Veneer
 - Customer Supplied*
- * Material subject to Kwik-Wall approval

Vertical Panel Joints

- Trimless
- Capped Trim

Top Seals

- Fixed
- Operable

Bottom Seals

- Fixed
- Adjustable Fixed
- Operable
- Automatic
- Extended

Available Options

Storage pocket doors; ADA Pass Doors – (single, double with panic hardware, concealed door closures & exit signs); invisible hinges; dry marker surfaces; insulated glass unit inserts; tack surfaces.

Hufcor 600 Series operable walls have earned their legacy reputation. Recognized worldwide for their unparalleled quality, design flexibility, acoustic performance and lasting durability, providing exceptional sound control and operational performance in thousands of large, complex installations, for some of the most iconic convention centers and large hospitality facilities around the world.

Hufcor 641 (by Kwik-Wall) individual, OMNI-directional panel configuration, features panels that are 4" [101.6] thick, manufactured of a durable 16 ga. roll-formed steel frame, and standard steel skins for maximum durability and sound control. Single panel heights are available from 30'-0" to 41'-7" feet [9144 to 12675] – up to 60 feet [18288] with spliced panel construction.



Hufcor 641 Panel Weights

STC	lbs./sq.ft.	Kg/m2
50A	9.0 lbs./sq.ft.	[44 kg/m2]
52S	9.5 lbs./sq.ft.	[46.0 kg/m2]
54S	10.9 lbs./sq.ft.	[53.2 kg/m2]
56S	13.6 lbs./sq.ft.	[63kg/m2]



HUFCOR 641

More Information