



## MODEL 642 — HINGED-PAIRED PANELS

SECTION 10 22 26 OPERABLE PARTITIONS  
SECTION 10 22 39 FOLDING PANEL PARTITIONS



### Overview

#### Panel Type

- Individual Panels Curve & Diverter
- Individual Panels – Multi Directional
- Hinged-Paired
- Continuously-Hinged

#### Partition Operation

- Manual
- Electric

#### Stacking Configurations

- Centerline
- Offset
- Remote
- Bi-Parting

#### STC Options

A=Acoustic Substrate S=Steel Skin

- 50A
- 52S
- 54S
- 56S

#### Panel Finishes

- Vinyl
  - High Pressure Laminate
  - Fabric
  - Wood Veneer
  - Carpet
  - Customer Supplied\*
- \* Material subject to Kwik-Wall approval

#### Vertical Panel Joints

- Trimless
- Capped Trim

#### Top Seals

- Fixed
- Operable

#### Bottom Seals


- Fixed
- Automatic
- Adjustable Fixed
- Extended
- Operable

#### Available Options

Storage pocket doors; ADA Pass Doors – (single, double with panic hardware, concealed door closures & exit signs); invisible hinges; dry marker surfaces; insulated glass unit inserts; tack surfaces.

With a long history of exceptional operational and acoustical performance in large and complex layouts up to 60 feet tall, **Hufcor 600 Series** operable walls have earned their legacy reputation.

**Hufcor 642** paired panel configuration (by Kwik-Wall) features panels that are 4" [101.6] thick, at up 24'3" [7391] height, manufactured of a durable 16 ga. roll-formed steel frame, and standard steel skins for maximum durability and sound control. Panels are hinged in pairs allowing fast setup. They may be stacked at either or both ends of the track or in a storage pocket at room perimeters.



Hufcor 642 Panel Weights

STC	lbs./sq.ft.	Kg/m2
50A	9.0 lbs./sq.ft.	[44 kg/m2]
52S	9.5 lbs./sq.ft.	[46.0 kg/m2]
54S	10.9 lbs./sq.ft.	[53.2 kg/m2]
56S	13.6 lbs./sq.ft.	[63kg/m2]



More Information