PROUDLY U.S. OWNED AND U.S. MANUFACTURED!

Operable Walls by Kwik-Wall
Technical Data

3000 SERIES · 2000 SERIES · HUFCOR 600 SERIES

MODEL 3010 — Individual Panels, Curve and Diverter

SECTION 10 22 26 OPERABLE PARTITIONS
SECTION 10 22 39 FOLDING PANEL PARTITIONS



Overview

Panel Type
- [x] Individual Panels Curve & Diverter
- [ ] Individual Panels – Multi Directional
- [ ] Hinged-Paired
- [ ] Continuously-Hinged

Partition Operation
- [x] Manual
- [ ] Electric

Stacking Configurations
- [ ] Centerline
- [x] Offset
- [x] Remote
- [ ] Bi-Parting

STC Options
A=Acoustic Substrate S=Steel Skin

- [x] 46A
- [x] 46S
- [x] 48A
- [x] 50A
- [x] 50S
- [x] 52S
- [ ] 54S
- [x] 56S

Panel Finishes
- [x] Vinyl
- [x] Fabric
- [x] Carpet
- [x] High Pressure Laminate
- [x] Wood Veneer
- [x] Customer Supplied*

* Material subject to Kwik-Wall approval

Vertical Panel Joints
- [x] Trimless
- [x] Capped Trim

Top Seals
- [x] Fixed
- [ ] Operable

Bottom Seals
- [ ] Fixed
- [x] Adjustable Fixed
- [x] Operable
- [x] Automatic
- [x] Extended

Available Options
Storage pocket doors; ADA Pass Doors – (single, double with panic hardware, concealed door closures & exit signs); invisible hinges; dry marker surfaces; insulated glass unit inserts; (GL Panels); tack surfaces.

KWIK-WALL's Model 3010 / 3010GL – Individual panels with pre-programmed-travel paths utilizing ultra-smooth radius curve and diverter track system which eliminates operator set up errors. Ideally suited for complex layouts and stacking configurations in applications up to 30'-0" [9144] in height. STC options from 46-56, Series 3000 operable walls offer industry-leading sound control

Model **3010** construction features panels that are 4" [101.6] thick, with a frame manufactured of durable roll-formed steel, and for maximum strength and sound control steel skins are standard. Optional insulated glass units 3010 GL are available with 43 and 48 STC.

Radius Curve
& Diverter Track

3000 Series Panel Weights

STC	lbs./sq.ft.	Kg/m2
46A	6.6 lbs./sq.ft	[32 kg/m2]
46S	8.5 lbs./sq.ft	[41 kg/m2]
48A	7.5 lbs./sq.ft	[37 kg/m2]
50A	9.0 lbs./sq.ft	[44 kg/m2]
50S	9.5 lbs./sq.ft	[46 kg/m2]
52S	9.5 lbs./sq.ft	[46 kg/m2]
56S	12.9 lbs./sq.ft	[63kg/m2]

3010/3010GL

More Information

Dimensions in [ ] are millimeters. Visit Kwik-Wall.com for additional product information and to connect with your authorized Kwik-Wall distributor.