



3000 SERIES · 2000 SERIES · HUF COR 600 SERIES

MODEL 3020 — Individual Multi-Directional Panels

SECTION 10 22 26 OPERABLE PARTITIONS
SECTION 10 22 39 FOLDING PANEL PARTITIONS



Overview

Panel Type

- Individual Panels Curve & Diverter
- Individual Panels – Multi Directional
- Hinged-Paired
- Continuously-Hinged

Partition Operation

- Manual
- Electric

Stacking Configurations

- Centerline
- Offset
- Remote
- Bi-Parting

STC Options

A=Acoustic Substrate S=Steel Skin

- 46A 50S
- 46S 52S
- 48A 54S
- 50A" 56S

Panel Finishes

- Vinyl High Pressure Laminate
 - Fabric Wood Veneer
 - Carpet Customer Supplied*
- * Material subject to Kwik-Wall approval

Vertical Panel Joints

- Trimless
- Capped Trim

Top Seals

- Fixed
- Operable

Bottom Seals


- Fixed Automatic
- Adjustable Fixed Extended
- Operable

Available Options

Storage pocket doors; ADA Pass Doors – (single, double with panic hardware, concealed door closures & exit signs); invisible hinges; dry marker surfaces; insulated glass unit inserts; (GL Panels); tack surfaces.

KWIK-WALL's Model 3020 / 3020GL – featuring individual, multi-directional panels capable of making 90° turns at X, L, or T track intersections. With STC options from 46-56, 3000 Series Operable Walls offer industry-leading premium sound control.

Model **3020** construction features panels that are 4" [101.6] thick, manufactured of a durable roll-formed steel frame, and standard steel skins for maximum durability and sound control. Optional acoustical glass inserts, (**3020GL**) are available and achieve 43 and 48 STC sound control.



90° X, L, T intersections

3000 Series Panel Weights

STC	lbs./sq.ft.	Kg/m ²
46A	6.6 lbs./sq.ft	[32 kg/m ²]
46S	8.5 lbs./sq.ft	[41 kg/m ²]
48A	7.5 lbs./sq.ft	[37 kg/m ²]
50A	9.0 lbs./sq.ft	[44 kg/m ²]
50S	9.5 lbs./sq.ft	[46 kg/m ²]
52S	9.5 lbs./sq.ft	[46 kg/m ²]
56S	12.9 lbs./sq.ft	[63kg/m ²]



3020/3020GL

More Information