




**3000 SERIES** · 2000 SERIES · HUF COR 600 SERIES

## 3000 SERIES — Pocket Doors

SECTION 10 22 26 OPERABLE PARTITIONS  
SECTION 10 22 39 FOLDING PANEL PARTITIONS



### Overview

#### Pocket Door Types

- Bi-Fold Doors w/ Bulb Seal
- Single Door w/ Bulb Seal
- Single Door w/ Expander
- Double Doors w/ Lap Trim
- Double Doors w/ Expander
- Double Doors w/Expander & Interlock Switches (3050 models)

#### Operation

- Manual
- Electric: Safety Interlock disables electric operable wall operation when pocket doors are closed.

#### STC Options

A=Acoustic Substrate S=Steel Skin

- |   |   |
|---|---|
| <input checked="" type="checkbox"/> 46A | <input checked="" type="checkbox"/> 50S |
| <input checked="" type="checkbox"/> 46S | <input checked="" type="checkbox"/> 52S |
| <input checked="" type="checkbox"/> 48A | <input type="checkbox"/> 54S            |
| <input checked="" type="checkbox"/> 50A | <input checked="" type="checkbox"/> 56S |

#### Panel Finishes

- |  |  |
|--|--|
| <input checked="" type="checkbox"/> Vinyl  | <input checked="" type="checkbox"/> High Pressure Laminate |
| <input checked="" type="checkbox"/> Fabric | <input checked="" type="checkbox"/> Wood Veneer            |
| <input checked="" type="checkbox"/> Carpet | <input checked="" type="checkbox"/> Customer Supplied*     |
- \* Material Subject to Kwik-Wall approval

#### Vertical Panel Joints

- Trimless
- Capped Trim

#### Top Seals

- Fixed: seals against pocket door header trim
- Operable

#### Bottom Seals

- |   |                                    |
|---|------------------------------------|
| <input checked="" type="checkbox"/> Fixed | <input type="checkbox"/> Automatic |
| <input type="checkbox"/> Adjustable Fixed | <input type="checkbox"/> Extended  |
| <input type="checkbox"/> Operable         |                                    |

#### Security Hardware Options

- Keyed Cylinder Lock with adjustable concealed vertical rod interfacing with strike plate attached to finished floor.
- Master Keyed Cylinder Lock (optional), furnished by others and installed by KWIK-WALL as noted on submittal shop drawings.

KWIK-WALL's **3000 Series Pocket Doors** close off your operable wall storage area when panels are not in use. Constructed with the same materials as our **3000 Series** operable wall panels, 3000 Series pocket doors can also serve as the perimeter wall for your final closure to seal against. In very wide openings, sealing to the face of the pocket door can eliminate panels without compromising the acoustic integrity of your operable wall.

**Series 3000 Pocket Doors** are 4" [101.6] thick, manufactured of a durable roll-formed steel frame, and standard steel skins for maximum durability and sound control.



3000 Series Panel Weights

STC	lbs./sq.ft.	Kg/m2
46A	6.6 lbs./sq.ft	[32 kg/m2]
46S	8.5 lbs./sq.ft	[41 kg/m2]
48A	7.5 lbs./sq.ft	[37 kg/m2]
50A	9.0 lbs./sq.ft	[44 kg/m2]
50S	9.5 lbs./sq.ft	[46 kg/m2]
52S	9.5 lbs./sq.ft	[46 kg/m2]
56S	12.9 lbs./sq.ft	[63kg/m2]



3000 SERIES  
More Information