




MODEL 2010 — Individual Panels, Curve and Diverter

SECTION 10 22 26 OPERABLE PARTITIONS SECTION 10 22 39 FOLDING PANEL PARTITIONS



Overview

Panel Type

- Individual Panels Curve & Diverter
- Individual Panels – Multi Directional
- Hinged-Paired
- Continuously-Hinged

Partition Operation

- Manual
- Electric

Stacking Configurations

- Centerline
- Offset
- Remote
- Bi-Parting

STC Options

A=Acoustic Substrate S=Steel Skin

- 42A 49S
- 45A 50A
- 49A 51S

Panel Finishes

- Vinyl High Pressure Laminate
 - Fabric Wood Veneer
 - Carpet Customer Supplied*
- * Material subject to Kwik-Wall approval

Vertical Panel Joints

- Trimless
- Capped Trim

Top Seals

- Fixed
- Operable

Bottom Seals

- Fixed Automatic
- Adjustable Fixed Extended
- Operable

Available Options

Storage pocket doors; ADA Pass Doors – (single, double with panic hardware, concealed door closures & exit signs); dry marker surfaces; insulated glass unit inserts; (GL Panels); tack surfaces.

KWIK-WALL's Model 2010 / 2010GL – featuring individual panels with pre-programmed-travel paths utilizing our ultra-smooth radius curve and diverter track system, eliminates operator set up errors. Ideally suited for complex layouts and stacking configurations in applications up to 16'-2" [4928] in height. With STC options from 42-51, Series 2000 operable walls offer industry-leading sound control.

Model **2010** construction features panels that are 3" [76.2] thick, manufactured of a durable roll-formed steel frame, and standard steel skins for maximum durability and sound control. Optional acoustical glass inserts, (**2010GL**) are available and achieve 38 STC sound control.



Radius Curve & Diverter Track

2000 Series Panel Weights		
STC	lbs./sq.ft.	Kg/m2
42A	6.5 lbs./sq. ft.	[32 kg/m2]
45A	8.5 lbs./sq. ft.	[41 kg/m2]
49A	9.0 lbs./sq. ft.	[44 kg/m2]
49S	10.9 lbs./sq. ft.	[53 kg/m2]
50A	9.0 lbs./sq. ft.	[44 kg/m2]
51S	11.0 lbs./sq. ft.	[54 kg/m2]



2010/2010GL

More Information